


*5+2 DAY PROGRAMMABLE THERMOSTAT
UP TO 4 TIME PERIODS PER DAY
1 HEAT / 1 COOL GAS/ELEC OR HEAT PUMP
SYSTEMS WITH NO AUX HEAT*

Product Features: PSP1152

- Battery or system powered
- 5+2 day programmable
- 1-Heat/1-Cool for use with gas/electric, heat pump with no AUX heat, electric & hydronic heat systems
- Extremely simple to operate and features a large, easy to read backlit, digital display
- Fahrenheit or Celsius display
- Compatible with 2, 3 or 4 wire systems
- Sleek styling and white color blend beautifully into any decor
- RC and RH terminals
- Bi-color LED indicator glows green or red to indicate cooling or heating
- Service filter indicator
- Easy access front battery compartment

PSP1100

- Battery or system powered
- Non-programmable
- 1-Heat/1-Cool for use with gas/electric, heat pump with no AUX heat, electric & hydronic heat systems
- Extremely simple to operate and features a large, easy to read digital display
- Fahrenheit or Celsius display
- Compatible with 2, 3 or 4 wire systems
- Sleek styling and white color blend beautifully into any decor
- RC and RH terminals
- Bi-color LED indicator glows green or red to indicate cooling or heating
- Easy access front battery compartment



* Complete warranty details available from your local branch.

TERMINAL DESIGNATIONS

Terminal Designations	
R	24 VAC Return
G	Fan Relay
W1	1 st Stage Heat Circuit
O/B	Reversing Valve
Y1	1 st Stage Compressor Relay
C	24 VAC Common

PRODUCT SPECIFICATIONS

Product Specifications: PSP1100 & PSP1152 Conventional (2H/2C) or Heat Pump (2H/2C)	
Electric Rating:	20-28VAC, 5 VA Max or (2) AA batteries
Output Rating:	Y1, W1, G, O/B – 500 mA
Control Range:	35° - 99° F (2° - 36° C)
Control Accuracy:	+/- 2° F (+/- 1° C)
Outputs:	Y1, G, W1, O/B